

## MXZ-3HJ50VA COOLING

Indoor units combination	Cooling capacity (kW)				Outdoor unit power consumption(kW)	Current (A)	Power factor(%)
	Unit A	Unit B	Unit C	Total			
25	2.50	-	-	2.50 ( 1.90 - 3.30 )	0.671 ( 0.571 - 0.847 )	2.95	99
35	3.15	-	-	3.15 ( 2.00 - 4.30 )	0.838 ( 0.585 - 1.204 )	3.68	99
50	5.00	-	-	5.00 ( 3.60 - 5.60 )	1.604 ( 1.110 - 1.693 )	7.04	99
25+25	2.30	2.30	-	4.60 ( 1.90 - 5.70 )	1.149 ( 0.537 - 1.271 )	5.05	99
25+35	2.08	2.92	-	5.00 ( 1.90 - 6.50 )	1.264 ( 0.537 - 2.620 )	5.55	99
25+50	1.67	3.33	-	5.00 ( 1.90 - 6.50 )	1.264 ( 0.547 - 2.610 )	5.55	99
35+35	2.50	2.50	-	5.00 ( 1.90 - 6.50 )	1.264 ( 0.537 - 2.620 )	5.55	99
35+50	2.06	2.94	-	5.00 ( 1.90 - 6.50 )	1.261 ( 0.557 - 2.595 )	5.54	99
25+25+25	1.67	1.67	1.67	5.00 ( 2.70 - 6.50 )	1.076 ( 0.666 - 2.296 )	4.73	99
25+25+35	1.47	1.47	2.06	5.00 ( 2.70 - 6.50 )	1.076 ( 0.666 - 2.296 )	4.73	99

## MXZ-3HJ50VA HEATING

Indoor units combination	Heating capacity (kW)				Outdoor unit power consumption(kW)	Current (A)	Power factor(%)
	Unit A	Unit B	Unit C	Total			
25	3.15	-	-	3.15 ( 3.15 - 4.50 )	0.956 ( 0.956 - 1.238 )	4.20	99
35	3.60	-	-	3.60 ( 3.60 - 4.50 )	1.108 ( 1.108 - 1.268 )	4.87	99
50	5.40	-	-	5.40 ( 3.70 - 7.90 )	1.462 ( 1.005 - 2.216 )	6.42	99
25+25	2.90	2.90	-	5.80 ( 1.70 - 7.50 )	1.309 ( 0.484 - 1.852 )	5.75	99
25+35	2.42	3.38	-	5.80 ( 1.70 - 7.50 )	1.309 ( 0.484 - 1.852 )	5.75	99
25+50	1.93	3.87	-	5.80 ( 1.70 - 7.50 )	1.259 ( 0.484 - 1.828 )	5.53	99
35+35	2.90	2.90	-	5.80 ( 1.70 - 7.50 )	1.309 ( 0.484 - 1.852 )	5.75	99
35+50	2.39	3.41	-	5.80 ( 1.70 - 7.50 )	1.182 ( 0.484 - 1.788 )	5.19	99
25+25+25	2.00	2.00	2.00	6.00 ( 2.40 - 7.50 )	1.250 ( 0.590 - 1.660 )	5.49	99
25+25+35	1.76	1.76	2.47	6.00 ( 2.40 - 7.50 )	1.250 ( 0.590 - 1.660 )	5.49	99